

## Hydraulic Power pack 22kW

Type: HPU-22-40-01

This unit is equipped with a variable axial plunger pump, with constant pressure control, which is driven by a 22kW 400V electric motor. The unit has an off-line filter and flush/cooling pump. The unit is easy to configure for all application by means of a proportional electric valve. In addition, there are also fixed connections for the Pressure, return and drain.

On the control box there is a possibility to extend the controls with an external start/stop and/or emergency stop device.

The frame around the unit is provided with lifting eyes and is easy to move around, by means of a forklift.

### Dimensions:

Height:	160 cm
Width:	110 cm
Depth:	130 cm
Weight:	900 kg



### Characteristics:

Fluid capacity:	300 litre
Pump displacement:	40cc
Max output flow:	58 L/min at 200 bar 34 L/min at 350 bar
Electric motor power:	22 kW 400VAC
Electrical connection	63A connector 5 poles, 3 phase + PE + N Connection for emergency stop Connection for remote control
Hydraulic connection	3/4" female quick coupling for the pressure 1" male quick coupling for the return 1/2" male quick coupling for the drain
Valve	Proportional valve, 4 sections, electrical or manually operated, with 1/2" quick couplings.
Facilities:	Air cooler Offline filter Flush pump

For more information, prices and availability please contact: 070-3902061 or send an e-mail to: [info@hydrau.nl](mailto:info@hydrau.nl)