

## Hydraulic power pack 5,5kW

Type: HPU-5,5-10-01

This unit is equipped with a gear pump, suspended in the oil, which is driven by a 5,5kW 400V electric motor. The unit is easy to operate for all applications by means of manually operated valve.

On the control box there is a possibility to extend the controls with an external start/stop and/or emergency stop device.

The frame of the unit is provided with lifting eyes and is by means of swivel wheels easy to move by hand. This makes this unit very practical for work in a workshop.

### Dimensions:

Height:	119 cm
Width:	47 cm
Depth:	78 cm
Weight:	180 kg



### Characteristics:

Fluid capacity:	77 litre
Pump displacement:	10cc
Max output flow:	15 L/min at 200 bar
Electric motor power:	5,5 kW 400VAC
Electrical connection	16A connector 5 poles, 3 phase + PE + N Connection for emergency stop Connection for remote control
Hydraulic connection	½" female quick coupling for the pressure ½" male quick coupling for the return ½" male quick coupling for the drain
Valve	Manually operated two-way valve with ½" quick couplings.
Facilities:	Swivel wheels Lifting eyes

For more information, prices and availability please contact: +31(0)70 3902061 or send an e-mail to: [info@hydrau.nl](mailto:info@hydrau.nl)